

Elevator Links

WELDLESS LINKS

King Oil Tool's forged steel alloy elevator links are especially designed for long life and safety.

Each weldless link is forged from a single steel billet, heat treated for Sets to maintain elevator balance. Links $3\frac{1}{2}$ " and $2\frac{3}{4}$ " are designed for intermediate to deep drilling and workover, rated 500 ton and 350 ton per set.

Maverick stocks 250 ton links in the following lengths: 72", 84", 96", 108" and 120" with 2 1/4" stock.

We also stock the following in 150 Ton: 48", 60", 72", 84", 96", 108" and 120" with 1 3/4" stock.



	PERFECTION LINKS				
PART #	SIZE: DIA x LENGTH	RATED CAPACITY*	WEIGHT**		
EB225-120	2 1/4" x 120"	250	700		
EB225-108	2 1/4" x 108"	250	610		
EB225-96	2 1/4" x 96"	250	550		
EB225-84	2 1/4" x 84"	250	550		
EB225-72	2 1/4" x 72"	250	515		
EBB175-120	1 3/4" x 120"	150	515		
EBB175-108	1 3/4" x 108"	150	470		
EBB175-96	1 3/4" x 96"	150	420		
EBB175-84	1 3/4" x 84"	150	330		
EBB175-72	1 3/4" x 72"	150	290		
EBB175-60	1 3/4" x 60"	150	245		
EBB175-48	1 3/4" x 48"	150	205		
EBB175-36	1 3/4" x 36"	150	165		

*PER SET TONS
**PER SET POUNDS





Elevator Links

PERFECTION LINKS

The Perfection Links are designed for light loads and Made from alloy steel, heat treated and magnetic particle inspected. Links have a rated capacity ranging from 20 tons through 80 tons per set of two.



OILFIELD SPECIALTIES INCORPORATED

PERFECTION LINKS				
PART #	SIZE: DIA x LENGTH	RATED CAPACITY*	WEIGHT**	
87518	· 7/8" x 18"	20	15	
87524	7/8" x 24"	20	20	
12518	1 1/4" x 18"	50	30	
12526	1 1/4" x 26"	50	41	
12530	1 1/4" x 30"	50	47	
15024	1 1/2" x 24"	60	60	
15030	1 1/2" x 30"	60	72	
15036	1 1/2" x 36"	60	84	
18030 .	1 3/4" x 30"	80	98	
18036	1 3/4" x 36"	80	113	
18042	1 3/4" x 42"	80	130	
18060	1 3/4" x 60"	80	180	

*PER SET TONS
**PER SET POUNDS

