

## Tubing Blocks

### SERIES 80 STREAMLUX TUBING BLOCKS WITH LOCKING DUPLEX SWIVEL HOOK

- Exclusive E-Z\* opening guards, no bolts to pull out and lose. Feature gives fastest possible exposure of sheave cluster for quick reeving.
- Extremely short overall length, extra weight, and excellent balance for fast non-wobbling falls.
- Extra large sealed sheave bearing diameters for fully rated capacities.
- Tapered roller thrust bearing in hook.
- Duplex hook for easy elevator operation, locks in six or eight positions.
- Convenient rod hook clevis available as shown on Figure 82A.
- Completely streamlined, no projections.
- Alloy flame hardened sheaves grooved for proper wire line size.
- Threaded hook parts precision machined and individually fitted for maximum safety.
- Hook assembly interchangeable with the Series 70 Streamlux Tubing Blocks.
- All blocks available with additional cheek weights.



SPECIFICATIONS						
FIG. #	SHEAVE SIZE	# OF SHEAVES	RECOMMENDED WIRE ROPE SIZE	API WORKING LOAD	WEIGHT (LBS.)	
					STANDARD	WEIGHTED
82	14"	2	5/8" - 3/4"	25 TONS	450	635
83	14"	3	5/8" - 3/4"	35 TONS	600	800
82	17"	2	3/4" - 7/8"	40 TONS	880	1200
83	17"	3	3/4" - 7/8"	50 TONS	1110	1430
82	20"	2	7/8" - 1"	50 TONS	1150	1625
83	20"	3	7/8" - 1"	75 TONS	1600	2075
82	24"	2	1" - 1 1/8"	75 TONS	1830	2490
83	24"	3	1" - 1 1/8"	100 TONS	2250	2910
83	30"	3	1" - 1/4"	150 TONS	2750	3850
84	24"	4	1" - 1 1/8"	100 TONS	2750	3360
84	30"	4	1" - 1/4"	150 TONS	3850	5050



## Tubing Blocks

### SERIES 70 STREAMLUX TUBING BLOCKS WITH LOCKING DUPLEX SWIVEL HOOK

- Spring loaded duplex hook assuring ample travel for efficient tubing operations. No load carrying threads.
- Exclusive E-Z\* opening guards, no bolts to pull out and lose. Feature gives fastest possible exposure of sheave cluster for quick reeving.
- Extremely short overall length, extra weight, and excellent balance for fast non-wobbling falls.
- Extra large sealed sheave bearing diameters for fully rated capacities.
- Tapered roller thrust bearing in hook.
- Duplex hook for easy elevator operation, locks in six or eight positions.
- Convenient rod hook clevis available as shown on Figure 72A.
- Completely streamlined, no projections.
- Alloy flame hardened sheaves grooved for proper wire line size.
- Threaded hook parts precision machined and individually fitted for maximum safety.
- Hook assembly interchangeable with the Series 80 Streamlux Tubing Blocks.
- All blocks available with additional cheek weights.



SPECIFICATIONS						
FIG. #	SHEAVE SIZE	# OF SHEAVES	RECOMMENDED WIRE ROPE SIZE	API WORKING LOAD	WEIGHT (LBS.)	
					STANDARD	WEIGHTED
72	14"	2	5/8" - 3/4"	25 TONS	540	740
73	14"	3	5/8" - 3/4"	35 TONS	720	920
72	17"	2	3/4" - 7/8"	40 TONS	1120	1440
73	17"	3	3/4" - 7/8"	50 TONS	1400	1720
72	20"	2	7/8" - 1"	50 TONS	1460	1935
73	20"	3	7/8" - 1"	75 TONS	1950	2425
72	24"	2	1" - 1 1/8"	75 TONS	2160	2820
73	24"	3	1" - 1 1/8"	100 TONS	2750	3410
73	30"	3	1" - 1 1/4"	150 TONS	3950	5050
74	30"	4	1" - 1 1/8"	150 TONS	4400	5500

